

## Bike Tire Fix

### Description

Special combination of active ingredients for first aid on flat tires without unmounting. Repairs flat tires without having to remove tire. Not usable on slit inner tubes, tires with lateral slits or when tire has slipped off of rim.

### Properties

- subsequent tire repair possible
- rapid remedy for punctures without dismantling
- simple to use

### Technical data

Base	Kautschuklösung / Rubber solution
Color / appearance	weißlich / whitish
Odor	Charakteristisch / characteristic
Propellant	Propan, Butan / propane, butane

Shelf life in original sealed container 24 months

### Areas of application

For first aid for tire punctures on bicycle tires from 12 to 29 inches. For tubeless and standard bicycle tires. Can be used for all common bicycle valves (Schrader, Presta and Dunlop valves).

### Application

Where possible, remove any causes of the puncture first (e.g. nails, screws). Then bring the wheel with the valve into the 12 o'clock position and deflate fully. Shake the can well, screw the screw connector onto the tire valve, hold the can vertical and use the entire can. Then remove the can and wipe off excess material. Finally, adjust the tire air pressure and take off immediately so that the foam can be distributed evenly. Depending on the size of the puncture, it may be necessary to pump more air after a few minutes. In most cases, a solid plug sealing the hole will have formed after 10 minutes.

### Comment

**Do not forget to go to a workshop to have the tire professionally repaired.**



### Available pack sizes

75 ml Can aerosol	6056 D-GB-E-F-I
75 ml Can aerosol	20719 GB-DK-FIN-N-S

**Our information is based on thorough research and may be considered reliable, although not legally binding.**